

Right Plywood

left and right angle:

1' 4 15/16" x 24, 8 7/16" x 12

- 350 3' 6 3/8" x 1' 11 7/8"
- 351 3' 6 3/8" x 1' 11 7/8"
- 352 2' 9 7/8" x 1' 11 7/8"
- 353 2' 9 7/8" x 1' 11 7/8"

- 354 5' 10 3/4" x 1' 11 7/8"
- 355 5' 10 3/4" x 1' 11 7/8"
- 356 4' 7 7/8" x 1' 11 7/8"
- 357 4' 5/8" x 1' 11 7/8"
- 358 3' 9 11/16" x 1' 11 7/8"
- 359 4' 11" x 1' 11 7/8"

- 360 6' 1 7/8" x 1' 11 7/8"
- 361 5' 4 1/2" x 1' 11 7/8"
- 362 5' 1 3/4" x 1' 11 7/8"
- 363 6' 4 15/16" x 1' 11 7/8"

- 364 4' 10 15/16" x 1' 11 7/8"
- 365 6' 5 3/4" x 1' 11 7/8"

- 366 3' 6 1/16" x 2' 4 11/16" ((wider than others))

- 367 6' 2 5/8" x 1' 11 7/8"
- 368 5' 2 5/16" x 1' 11 7/8"

- 369 7' 7 1/4" x 4 3/8" Gable Width Ruler
- 370 7' 6 3/4" x 4 3/8" Gable Width Ruler
- 371 7' 3 5/8" x 4 3/8" Gable Width Ruler
- 372 5' 5 13/16" x 4 3/8" Gable Width Ruler

Right Bevel Cut

- 301a 8' 11 3/8" :Adjusted to fit window
- 301b 8' 10 5/16"
- 301c 6 15/16" :Adjust to fit window
- 302 8' 2 3/8"
- 303 7' 3 1/16"
- 304 6' 3 3/4"
- 305 5' 4 9/16"
- 306 4' 5 1/4"
- 307 3' 7 13/16"
- 308 2' 10 5/16"
- 309 1' 11 1/4"
- 310 7' 4 1/8"
- 311 7' 8 11/16":bottom bevel
- 312a 8' 11 3/8" :Adjusted to fit window
- 312b 8' 10 5/16"
- 312a 6 15/16" :Adjust to fit window
- 313 8' 4 1/2"
- 314 7' 5 1/4"
- 315 6' 6"
- 316 5' 6 11/16"
- 317 4' 7 7/16"
- 318 3' 8 1/8"
- 319 2' 8 7/8"
- 320 1' 10 3/4"
- 321 7' 1/2"
- 322 8' 1/4":bottom bevel

- 329 1' 4 1/16" :Adjust to fit window
- 330 1' 4 1/16" :Adjust to fit window

Right Square Cut

- 323 3' 6 3/8":rightHeader, Adjust to fit
- 324 3' 1/8"

- 325 7' 10":double 2x4
- 326 7' 10":double 2x4
- 327 2' 7 5/8":Adjust to fit window
- 328 2' 7 5/8":Adjust to fit window
- 331 3' 6 3/8"

Right gable end supports

- 332 3' 4" square cut
- 333 1' 4 3/4" right bevel
- 334 2' 6 3/16" right bevel
- 335 4' 4" square cut
- 336 1' 4 11/16" right bevel
- 337 2' 6 3/16" right bevel

Right Front valley lift

- V2-1 2' 3/4" square cut
- V2-2 2' 2 1/8" square cut
- V2-3 1 3/4" x 6 1/4"wide x 9 5/16" x 1' 5/16"
diagonal cut
Grind top corners to eliminate point load.

Right Back valley lift

-V3-1 2' 3/4" square cut

-V3-2 2' 2 3/16" square cut

V3-3 6 3/8"wide x 1 3/4"thick x 9 1/4" x 1' 5/16"
diagonal cut

Grind top corners to eliminate point load.

Right ridge beam support post

On top of window header

2 5/16" x 10 7/16" x 3 1/2"